FABRIC MESH BANNERS

Artwork specifications

1 Set the finished size

Supply a PDF at 100% of your ordered width and height. No bleed is required. Do not include crop, trim or registration marks. Online sizes: 300-10000mm wide and 300-2700mm high.

2 Leave the edges clear

Keep text, logos and important content at least 30mm inside all four edges, clear of eyelets, hems and stitching. Backgrounds should fill the entire finished size.

3 Prepare type and images

Use CMYK colour. Outline all fonts and embed all images and placed elements. Bitmap images must be at least 130 DPI at final printed size. Use PANTONE+ Solid Coated swatches for required colour references; exact printed matching is not guaranteed.

4 Use the correct template

Choose the PDF matching your ordered finished size. It has a removable, non-printing Guides layer showing the 30mm safe area. Place your artwork on a new layer. Delete the Guides layer before exporting the production PDF. For custom sizes, use the same finished-size and 30mm clearance rules.

5 Check the product and proof

Single-sided dye-sublimated print on 120gsm polyester mesh. Edges have 25mm webbing reinforcement. Optional stainless-steel eyelets are at corners and a maximum of 500mm or 1000mm apart. Allow 2-3% finished-size variation from sewing. QR codes are not recommended on perforated fabric.

6 Supply your artwork

Upload your production PDF with your Platinum Signs order, one file per design. Choose artwork assistance if preparation is needed. Check dimensions, spelling, images, colours and finishing before approving the proof.